AS Tutorial Creating Sandwich White Jobs for Tauro

This tutorial demonstrates how to create sandwich white jobs for different applications. It also explains how you can control the order of the printer layers using the correct calibrated print modes.

Download the Asanti Sample Files via the Asanti Client: Help > Asanti Online > Download Sample Files. Some exercises require an ink set with Primer.

1. Process a job with concurrent or sequential print layers.

This exercise explains the difference between printing layers concurrently and sequentially.

- 1. File > New Wide Format Job.
- 2. In the Media inspector select these settings:
 - Printer Tauro.
 - Size: 600 mm x 600 mm.
 - Quality: Standard.
 - Enable White (1).
 - Fill Entire Image and Sandwich-white (On Media Calibration).
 - If available, enable Primer (2): select Fill Entire Image.
- 3. Import "Agfa_logo_color.jpg".
- 4. Place the product to the sheet.
- 5. Mirror the product on the sheet.
- 6. Context click the placed product > Step and Repeat> Copies: Fill Entire Grid.
- 7. Click the Printer Parameters button (3). All Layers have identical printer parameters.
- 8. Click Cancel.
- 9. Submit job, name the job "Primer-Color-White-Color-Concurrent" and select "Make and send to Printer".

Note:

- Tauro H2500 supports up to 4 layers.
- Tauro H3300 and UHS support up to 5 & 6 layers.

	Print Mod	e Parameters	Layers ha	ave identio	cal printer p	arar	neters	
Application			Color On Media		White		Primer	
		Resolution]	635x1200 🔻		635x1200 💌	
▼ 🗹 White (1) Sandwich-white (On Media calibrat	ion),	ber of passes	8 🗸		8 🗸		8 🗸	
Fill Entire Image	\sim	Direction	Bi-Directional -		Bi-Directional 👻		Bi-Directional -	
The Endle Enlage	*	Screener	Tilebased 💌		Tilebased 🔻		Tilebased 🔻	
Sandwich-white (On Media calibration)	\sim	Screen			APS_DOT_5		APS_DOT_5 👻	
	_	oplets per dot]	0 1DPD 👻]	01DPD 👻	1
Choke (4px) V Opacity: 100,0	%	UV Leading UV Trailing		%	80	%	0	%
		Masking Mode		/6	Flat 🔻	/0	Flat 🗸	/0
(2)		Mask		%	0	%	0	%
✓ ☑ Primer (2) Fill Entire	Image	Print Density	100		100		100	
Fill Entire Image	~	tle Outside of:	Image 💌		Image 💌		Image 🔹	
	_	: Mode Option						
Choke (4px) V Opacity: 100,0	%	meters						
			Anti-static	5				
			Input Roller Bar	5				
Calibrated Printing Mode			Output Roller Bar	*				
		: Adjustment	Media Sensitive to heat	: າ Jum າ				
Std - 8P Bi 635x1200 APS - 6C	~	ra Head Gap		um 🤊				
2)								
Printer Parameters (3)							OK Can	cel


A Printer Parameters



Software version: Asanti 6.x

Document version: October 12, 2023

Select the job in the Tauro client. The concurrent layers are marked in the Job Name (1): P+W+C+P and visualized as layers in the print task pane (2). The media will be printed in 1 print run (=concurrent printing).



White can be visualized as a color e.g. yellowish in the thumbnails on Tauro.

- 11. Go back to the Asanti client and duplicate job "Primer-Color-White-Color-Concurrent".
- 12. Open the printer parameters and change the number of passes

of Primer to 2.			
A Printer Parameters			×
Print Mode Parameters			
	Color On Media	White	Primer
Resolution	635x1200 🔻	635x1200 👻	635x1200 👻
Number of passes	8 🔻	8 🔻	2 🗸

- 13. Click OK and Submit Job, Use "2p Primer+8p Color-White-Color" as job name.
- 14. In the Tauro client, select job "2p Primer+8p Color-White-Color". This job has now 2 print layouts and will be printed in 2 print runs (= sequential printing).
 - The first Print run (1) contains primer (2 pass).
 - The second Print run (2) is C+W+C (8 pass).



To print different layers concurrent, select equal print mode settings in Asanti.


2. C1-W-C1 Sandwich white on the backside of media

This application is also known as day and night printing at the backside of transparent media. Two identical products are printed with a white layer in between. The first product is printed mirrored on the media; the second layer is a post white layer. The third layer contains the same product as the first layer. The printed product is viewed through the media. During the day the first 2 layers produce a good print and color result. The 3th layer increases the product density when the light at the back is enabled during the night. The color output during the night and day should look equal.


Print Result	Print Run 1
Media-C1-W- C1	C1-W-C1 = Sandwich white (on media calibration)


- 1. File > New Wide Format Job.
- 2. In the Media inspector select these settings:
 - Printer: Tauro.
 - Media: Generic (or a transparent media).
 - Media size 500 x 500 mm.
 - Select White, solid Image Mask, sandwich-white (On Media Calibration).
 - Calibrated Print Mode: e.g. Std- 8P Bi 635x1200 APS 6C.
- 3. Import product CHIMAY.jpg.
- 4. In the positioning tool bar set scaling to 300%.
- 5. Drag the product to the sheet.
- 6. **Mirror** the product.
- 7. Submit job, name the job "Sandwich white on backside" and select "Make and send to Printer".
 - The "on media" Calibrated Print Mode and print mode parameters are used for the color layer (C1).
 - The "White" Calibrated Print Mode and print mode parameters are used for the white layer (W).
- 8. Print the job in the Tauro client. The Tauro job contains 3 layers.
 - All 3 layers will be printed in 1 print run (=concurrent printing).





Application		
🗢 🖂 White	Sandwich-white (On Media calibration	on),
Solid Image	Mask	\sim
Sandwich-w	hite (On Media calibration)	\sim
Choke (4px) v Opacity: 100,0	%






3. C1-W-C1 Sandwich white on the front side of media

This application is also known as day and night printing at the front side of transparent media. Two identical products are printed with a white layer in between. The first product is printed on the media but is not directly visible because a white layer is printed on top. This second layer is a pre-white layer and the 3th layer is printed on the white layer. During the day the first 2 layers produce a good print result. The 3th layer increases the product density when the light at the back is enabled during the night. The color output during the night and day should look equal. You look directly to the printed product (Not through the media).

Print Result	Print Run 1
C1-W-C1-	C1-W-C1 = Sandwich white (on white calibration)
Media	

- 1. File > New Wide Format Job.
- 2. In the Media inspector select these settings:
 - Printer: Tauro.
 - Media: Generic.
 - Media size 500 x 500 mm.
 - Select White, solid Image Mask, Sandwich-white (On White Calibration).
 - Calibrated Print Mode: e.g. Std- 8P Bi 635x1200 APS 6C.
- 3. Import product CHIMAY.jpg.
- 4. In the positioning tool bar set scaling to 300%.
- 5. Drag the product to the sheet. Don't mirror the product.
- 6. Submit job, name the job "Sandwich white on front side" and select "Make and send to Printer".
 - The "on white" Calibrated Print Mode and print mode parameters are used for the color layer (C1).
 - The "White" Calibrated Print Mode and print mode parameters are used for the white layer (W).
- 7. Print the job in the Tauro client. The Tauro job contains 3 layers. All 3 layers will be printed in 1 print run (=concurrent printing).

ToPrint	Order	Separation
×	1	Color (C1)
×	2	White (W)
×	3	Color (C1)



	Application	
~	White Sandwich-white (On White calibration	n), S
	Solid Image Mask	\sim
	Sandwich-white (On White calibration)	\sim
	Choke (4px) V Opacity: 100,0	%

4. C1-W-C2-W-C3 Block out application in 2 print runs

Following Combinations of print runs are possible:

Print Result	Print Run 1	Print Run 2
Media-C1-W- C2(Black) -W-C3	C1-Postwhite	C2(Black) - Prewhite-C3
C1-W- C2(Black) -Media-W-C3	C2(Black) - Prewhite-C1	PreWhite-C3
C1-W-Media- C2(Black) -W-C3	PreWhite-C1	C2(Black) - PreWhite-C3
Media-C1-W- C2(Black) -W-C3	C1-W- C2(Black) -W-C3	/
Media-Primer-C1-W- C2(Black) - W-C3	Primer-C1-W- C2(Black) -W-C3	/


For this exercise, the job is printed on Tauro in 2 print runs and all layers will be printed on the backside of the media (Media-C1-W- C2(Black) -W-C3).

Create print run1 (C1-W).

In Asanti, a sheet cannot contain multiple color layers (e.g. C1 and C2). Multiple jobs are needed to accomplish that. Job 1 contains the first 2 layers: the color product layer and a post white layer. To achieve optimal adhesion in this application it is advised to end the first print run with a white layer.

- 1. File > New Wide Format Job.
- 2. In the Media inspector select these settings:
 - Printer: Tauro .
 - Size: 1000 x 700 mm.
 - Quality: e.g. High Definition.
 - Enable White.
 - Set Fill Entire Image.
 - Set Post-White (On Media calibration).
 - Calibrated Print Mode: HighD-12p Bi 725x1200 AQS 6C.
- 3. Import product disco_ball_600x400.jpg.
- 4. Drag the product to the sheet.
- 5. **Mirror** the product.
- 6. Submit job, name the job "Block out application run1" and select "Make and send to Printer".

	Application			
~	🗹 White	Post-white (C	On Media calibration), Fi	ll En
	Fill Entire Ima	age		\sim
	Post-white (On Media cal	ibration)	\sim
	Choke (4	łpx) 🗸	Opacity: 100,0	%



Create print run2 (C2-W-C3)

For print run 2, 2 jobs must be created in Asanti. Because these Asanti jobs must be printed in 1 print run, they must be merged in the Tauro client. To merge 2 Asanti jobs on Tauro, a name convention must be used for the job name: jobname#comment;

- Each job name must end with a #
- The name used before the # has to be identical for each job that needs to be merged.
- A comment must be added after the **#**. The comment needs to end with a ;


The comment is used to indicate the print layer names.

- 1. In Asanti, duplicate the job "Block out application run1".
- 2. Context click the frame > Clear Frame.
- 3. Delete Disco_ball_600x400.jpg from the available products pane.
- 4. Import "black.jpg".
- 5. Drag "black.jpg" to the empty frame.
- 6. Media Inspector: Uncheck White.
- 7. Submit job, name the job "Block out application run2#K;" (Don't forget the ; at the end of the job name) and select "Make and send to Printer".

Job Name: Block out application run2#K;

Merged jobs on Tauro must have identical settings for:

- Sheet size, product size and position. When these are different, an error is given next to the Asanti job: Error Merging Job, Incompatible Sheets, Incompatible Sheet positions or alignment.
- Calibrating Print Modes
- Printer Parameters
- 8. In the Tauro client select the job "Block out application run2#K;". The job is in collecting state.






- 9. In the Asanti client, duplicate the job "Block out application run2#K;".
- 10. Context click the frame > Clear Frame.
- 11. Import product "CHIMAY BLEU.jpg".
- 12. Drag "CHIMAY BLEU.jpg" to the empty frame. The product is mirrored. Click mirror, so the product is placed right reading.
- 13. Select White, Fill Entire Image (Asanti), Pre-white (On White calibration).
- 14. Submit job, name the job "Block out application run2#PreWC;" and select "Make and send to Printer".

Job Name: Block out application run2#PreWC;

- 15. In the Tauro client, the original job is renamed to "Block out application run2#K;+PreWC;". Select the job. Tauro has merged the 2 jobs,
 - No collecting state is shown anymore.
 - The job shows 3 layers: C2 + W + C3.
- 16. Print job "Block out application run1".
- 17. Print job "Block out application run2#K;+PreWC;" on the same side of the media.




ToPrint	Order	Separation
x	1	Color C2
×	2	White ₩
×	3	Color C3

5. Primer-C1-W-C2-W-C3 Block out application in 1 print run

	Print Result	Print Run 1
	Media-C1-W- C2(Black) -W-C3	C1-W- C2(Black) -W-C3
ĺ	Media-Primer-C1-W- C2(Black) -W-C3	Primer-C1-W- C2(Black) -W-C3

To merge 2 jobs on Tauro, a simple name convention can be used for the job name in Asanti: my job name#LayerName; (see exercise 4. C1-W-C2-W-C3 Block out application in 2 print runs on page 6).



To merge more than 2 Asanti jobs on Tauro, an advanced name convention must be used for the Asanti job name: my job name(<nr of Asanti jobs>)#LayerName(<merge order>);

- The text before the # sign must be the same for all Asanti jobs that must be recombined in 1 Print Task on Tauro.
- The number between the first "()" must be set to the number of Asanti jobs that are merged into 1 Tauro job. E.g. when set to 3, Tauro will expect that 3 Asanti jobs will be merged in 1 print task in a Tauro job.
- The text after the # is different and is used in the Asanti job name to differentiate the jobs.
- The Asanti job name must end on a ";".
- The number between the last "()" must be set to a number. The Asanti job that must be merged first on Tauro must get number 1, the second 2...

The to-be-merged jobs need to use identical: Sheet size and position, Product size and position, CPM's, Printer Parameters

To use the advanced name convention Tauro 3300 is required.

For this exercise, the job is printed on Tauro in 1 print run and all layers will be printed on the backside of the media (Media-Primer-C1-W-C2(Black) -W-C3). This requires 3 Asanti jobs to be merged on Tauro. This means the advanced name convention must be used.

Create print run1 (Primer-C1-W-C2-W-C3).

- 1. Create a New Wide Format Job.
- 2. Select printer Tauro.
- 3. Select a CPM that has support for printing color on white e.g. Std 8P Bi 635x1200 APS CMYKck.
- 4. Enable White, Fill Entire Image, Post White.
- 5. Enable Primer, Fill Entire Image.
- 6. Set sheet size e.g. 500x400mm.
- 7. Select Cutter "None", Bleed 0 mm
- 8. Place an product on the Sheet e.g. ASANTI Visual 390x250.pdf.
- 9. Center the product on the sheet.
- 10. Mirror the product.
- 11. Submit job.
- 12. Enter the job name multilayer test(3)#PC1W(1);
- 13. Choose "make and send to printer".
- 14. Click Submit. The job on Tauro is locked because a second and a
 - third part are expected.



- 15. Duplicate the Asanti job.
- 16. Context click the product in the frame > Clear Frame.
- 17. File>Add product, open black.jpg.
- 18. Drag black.jpg to the empty frame
- 19. Uncheck White, uncheck Primer
- 20. Submit job
- 21. Change the job name to multilayer test(3)#C2(2);
- 22. Choose "make and send to printer".

Application		
Vite Post-white (On Media calibration), Fill	En
Fill Entire Image		•
Post-white (On Media ca	alibration)	•
Choke (4px) 🔻	Opacity: 100.0	%
♥ ♥ Primer	Fill Entire In	nage
Fill Entire Image		•
Choke (4px) 🔻	Opacity: 100.0	%


Job Name: multilayer test(3)#PC1W(1);

ToPrint	Order	Separation
×	1	Primer
×	2	Color
×	3	White

	Application
Þ	White
	Primer

- 23. Click Submit. The job on Tauro doesn't get updated yet because a third part is still expected.
- 24. Duplicate the last Asanti job.
- 25. Context click the frame on the sheet > Clear Frame.
- 26. File>Add products, open Disco_ball_600x400.pdf.
- 27. Drag Disco_ball_600x400.pdf to the empty frame
- 28. Turn of the Mirroring of the product on the sheet.
- 29. Check White, Fill Entire Image, Pre-white (On White calibration)
- 30. Submit job
- 31. Change the job name to multilayer test(3)#WC3(3);
- 32. Choose "make and send to printer".
- 33. Click Submit. The job on Tauro gets updated. It has 6 Print layers





ToPrint	Order	Separation
×	1	Primer
×	2	Color
×	3	White
×	4	Color
×	5	White
×	6	Color

Production Dashboard will show 3 jobs. When the job is printed on Tauro, actual values (ink, media usage, time) will be reported to the first job in Production Dashboard ("multilayer test(3)#PC1W(1);").

6. C1-W-C2 Sandwich white on backside with mirrored content

The product is viewed from both sides and will be printed on the backside of the transparent media.

Print Result	Print Run 1
Media-C1-W-C2	C1-PreWhite-C2

- 1. File > New Wide Format Job.
- 2. In the Media inspector select these settings:
 - Printer: Tauro.
 - Media: Generic (or a transparent media).
 - Quality: e.g. High Definition.
- 3. Import product "Disco_ball_600x400.jpg".
- 4. Drag the product to the sheet.
- 5. Mirror the product.
- Submit job, name the job "Sandwich white on backside Mirror#C1;" and select "Make and send to Printer".
- 7. Duplicate job "Sandwich white on backside Mirror#C1;"
- 8. Enable White.
- 9. Select Fill Entire Image.
- 10. Select Pre-white (On White Calibration).
- 11. The product placed on the layout is mirrored. Select the product on the sheet, reselect the mirror button to undo the mirror.
- 12. Submit job,


name the job "Sandwich white on backside Mirror#PreWC2;" and select "Make and send to Printer".

13. Tauro will merge these 2 jobs, print the merged job.



٦	ToPrint	Order	Separation
	×	1	Color C1
	×	2	White ₩
	×	3	Color C2





7. P-C1-W-C1 Sandwich white with Primer

Print Result	Print Run 1
Media-Primer-C1-W-C1	Primer-C1-W-C1 = Sandwich white (on Media calibration)
C1-W-C1-Primer-Media	Primer-C1-W-C1 = Sandwich white (on white calibration)

- 1. File > New Wide Format Job.
- 2. In the Media inspector select these settings:
 - Printer: Tauro.
 - Media: Generic (or a transparent media).
 - Quality: e.g. High Quality.
 - Select White, Fill Entire Image, Sandwich White on Media (print on backside) or on White (print on front side).
 - Enable Primer, Fill Entire Image.
- 3. Import product "Disco_ball_600x400.jpg".
- 4. Drag the product to the sheet.
- 5. Mirror the product if using Sandwich White on Media.
- 6. Submit job, name the job "Sandwich white with Primer" and select "Make and send to Printer". A job with 4 layers will be created and Tauro.
- 7. Print your job

8. P-C1-W-C2 Sandwich white with different content with Primer

Print Result	Print Run 1
Media-Primer-C1-W-C2	Primer-C1-PostWhite-C2

Create layers Primer-Color1- White

Primer is the first layer to be printed and therefor this job needs to be submitted first.

- 1. File > New Wide Format Job.
- 2. In the Media inspector select these settings:
 - Printer: Tauro.

	Application				
~	✓ White S	andwich-	white (On Med	lia calibratio	m),
	Fill Entire Image	2			\sim
	Sandwich-white	(On Me	dia calibratio	n)	\sim
	Choke (4px) ~	Opacity:	100	%
~	Primer			Fill Entire I	image
	Fill Entire Image	•			\sim
	Choke (4px)) ~	Opacity:	100	%

Order	Separation
1	Primer
2	Color
3	White
4	Color
	1 2 3

- Media: Generic (or a transparent media).
- Quality: e.g. High Quality.
- Select White, Fill Entire Image, Post-white (on media calibration).
- Select Primer, Fill Entire Image.
- 3. Import product "Disco_ball_600x400.jpg".
- 4. Drag the product to the sheet.
- 5. Mirror the product
- Submit job, name the job "Sandwich white Primer Mirror#PC1W;" and select "Make and send to Printer".

Job Name: Sandwich white Primer Mirror #PC1W;

	Application	
~	White Post-white (On Media calibration), Fill	En
	Fill Entire Image	\sim
	Post-white (On Media calibration)	\sim
	Choke (4px) V Opacity: 100,0	%
~	Primer Fill Entire In	nage
	Fill Entire Image	\sim
	Choke (4px) V Opacity: 100,0	%

Create layer Color 2

- 1. Duplicate the job "Sandwich white Primer Mirror#PC1W;".
- 2. Uncheck White and primer.
- 3. The product placed on the layout is mirrored. Select the product on the sheet, reselect the mirror button to undo the mirror.
- 4. Submit job,

name the job "Sandwich white Primer Mirror#C2;" and select "Make and send to Printer".

Tauro shows a job with 4 layers.

ToPrint	Order	Separation	#Done
×	1	Primer P	0
×	2	Color C1	0
×	3	White W	0
×	4	Color	0
		C2	